


| | | | | | | |
|---|---------|--------------|---------------|---|---------------------|--|
| | | DRAWN BY | DATE |  ATARI® | ATARI CORP. | |
| | | | | | 1196 Borregas | |
| | | | | | Sunnyvale, CA 94086 | |
| NEXT ASSY | USED ON | CHECKED | TITLE | | IC; CMOS MMU | |
| <p>NOTICE TO ALL PERSONS RECEIVING THIS DRAWING CONFIDENTIAL: Reproduction Forbidden without the specific written permission of Atari C Sunnyvale, California. This drawing is only conditionally issued, and neither receipt nor possession thereof confers or transfers any right in, or license to use, the subject matter of the drawing or any design or technical information shown thereon, nor any right to reproduce this drawing or any part thereof, except for manufacture by vendors for Atari Corp. and for manufacture under the corpora- tion's written license, no right to reproduce this drawing is granted or the subject matter thereof unless by written agree- ment with or written permission from the corporation.</p> | | ENGINEER | 12/4/84 | DRAWING NO. C061618A-XX | | |
| | | Pandy Hooper | | | | |
| | | APPROVED | | REV | | |
| | | APPROVED | | A | | |
| | | SCALE | SHEET 1 OF 11 | | | |

TABLE OF CONTENTS

- 1.0 SCOPE
- 2.0 APPLICABLE DOCUMENTS
 - 2.1 ATARI DOCUMENTS
- 3.0 ELECTRICAL REQUIREMENTS
 - 3.1 FUNCTIONAL BLOCK DIAGRAM
 - 3.2 LOGIC EQUATIONS
 - 3.3 PAL FUSE MAP
 - 3.4 PIN ASSIGNMENT
 - 3.5 ABSOLUTE MAXIMUM RATINGS
 - 3.6 RECOMMENDED OPERATING CONDITIONS
 - 3.7 D.C. ELECTRICAL CHARACTERISTICS
 - 3.8 SWITCHING CHARACTERISTICS
- 4.0 PACKAGE CONFIGURATION
- 5.0 MARKING
- 6.0 QUALITY ASSURANCE PROVISIONS
- 7.0 PACKAGE FOR SHIPMENT



ATARI CORP.

1196 Borregas Ave.

Sunnyvale, CA 94086

SIZE

DRAWING NO.

CO61618A-XX

REV

A

SCALE

SHEET 2 OF 11

1.0 SCOPE

This specification covers the electrical, packaging, marking, and quality requirements for a proprietary integrated circuit device. The component is for use in some of ATARI's 8-bit 6502 based computers. Its primary function is memory management and it is called, appropriately, a Memory Management Unit (MMU). This document addresses CMOS versions of the device. Bipolar Hard Array Logic (HAL) and Programmable Array Logic (PAL) versions are covered in C061618.

2.0 APPLICABLE DOCUMENTS

The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue in effect on date of latest revision of this specification shall apply.

2.1 ATARI Documents

| | |
|---------|--|
| C099901 | Qualification, Reliability Acceptance Specification for - Discrete Semiconductors and Integrated Circuits. |
| C099931 | 20-Lead, Dual in-line package. |



ATARI CORP.

1196 Borregas Ave.

San Jose, CA 95128

SIZE

DRAWING NO.

C061618A-XX

REV


A

SCALE

SHEET 3 OF 11

3.0 ELECTRICAL REQUIREMENTS

3.1 Functional Block Diagram



ATARI CORP.
1196 Borregas Ave.

SIZE

DRAWING NO.

CO61618A-XX

REV

A

3.2 Logic Equations

$$\overline{S4} \text{ (19)} = \overline{A13} * \overline{A14} * A15 * RD4 * REF$$

$$\overline{S5} \text{ (12)} = A13 * \overline{A14} * A15 * RD5 * REF$$

$$\overline{BCS} \text{ (13)} = A13 * \overline{A14} * A15 * \overline{RD5} * \overline{BEN} * REF$$

$$\overline{IO} \text{ (17)} = \overline{A11} * A12 * \overline{A13} * A14 * A15 * REF$$

$$\begin{aligned} \overline{OS} \text{ (15)} = & A13 * A14 * A15 * ROMEN * REF \\ & + \overline{A12} * A14 * A15 * ROMEN * REF \\ & + A11 * A12 * \overline{A13} * A14 * A15 * ROMEN * MPD * REF \\ & + \overline{A11} * A12 * \overline{A13} * A14 * \overline{A15} * ROMEN * \overline{MAP} * REF \end{aligned}$$

$$\begin{aligned} \overline{CI} \text{ (16)} = & \overline{A13} * \overline{A14} * A15 * RD4 * REF \\ & + A13 * \overline{A14} * A15 * RD5 * REF \\ & + A13 * \overline{A14} * A15 * \overline{RD5} * \overline{BEN} * REF \\ & + OS \\ & + \overline{A11} * A12 * \overline{A13} * A14 * A15 * REF \\ & + \overline{REF} \end{aligned}$$

LOGIC CONVENTION: When the right hand side of an equation is true or Logic 1, the left hand side is a Logic 0.



ATARI CORP.

1196 Borregas Ave.

SIZE

DRAWING NO.

CO61618A-XX

REV


A

SCALE

SHEET 5 OF 11

3.3 PAL Fuse Map (For Information Only)

Logic Diagram HAL16LB



ATARI CORP.
1196 Borregas Ave.
Sunnyvale CA 94086

| | | |
|-------|----------------------------|----------|
| SIZE | DRAWING NO. CO61618A-XX | REV A |
| SCALE | SHEET 6 OF 11 | |

3.4 Pin Assignment

Pin assignment shall be depicted as follows when related to package configuration.

| | | | |
|-------|----|----|------------------|
| A11 | 1 | 20 | VCC |
| A12 | 2 | 19 | $\overline{S4}$ |
| A13 | 3 | 18 | BEN |
| A14 | 4 | 17 | \overline{IO} |
| A15 | 5 | 16 | \overline{CI} |
| MAP | 6 | 15 | \overline{OS} |
| RD4 | 7 | 14 | MPD |
| RD5 | 8 | 13 | \overline{BCS} |
| ROMEN | 9 | 12 | $\overline{S5}$ |
| GND | 10 | 11 | REF |



ATARI CORP.

1196 Borregas Ave.
Sunnyvale, CA 94086

SIZE

DRAWING NO.

CO61618A-XX

REV

A

SCALE

SHEET 7 OF 11

3.5 Absolute Maximum Ratings

Absolute Maximum ratings in Free Air. Exceeding the "absolute maximum ratings", may result in failure or permanent damage to the part. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

| | |
|---|-------------------------|
| | Operating |
| Supply Voltage V_{CC} | 7V |
| Input voltage | 5.5V |
| Off-state output voltage | 5.5V |
| Storage temperature range | -65 to 150 degrees C |
| Output short circuit duration | Infinite |

3.6 Recommended Operating Conditions

| PARAMETER | SYMBOL | MIN | MAX | UNIT |
|------------------------------------|----------|------|------|------|
| Supply Voltage | V_{CC} | 4.75 | 5.25 | V |
| High-level output current (source) | I_{OH} | | -3.2 | mA |
| Low-level output current (sink) | I_{OL} | | 4.0 | mA |
| Operating free air temperature | T_A | 0 | 70 | °C |



ATARI CORP.

1196 Borregas Ave.

San Jose, CA 95128

SIZE

DRAWING NO.

CO61618A-XX

REV

A

SCALE

SHEET 2 OF 11

3.7 DC Electrical Characteristics
(TA=0 degrees C TO 70 degrees C)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | MAX | UNITS |
|------------------------------------|------------------|---|-----|-----|-------|
| High-level input voltage | V _{IH} | | 2.0 | | V |
| Low-level input voltage | V _{IL} | | | 0.8 | V |
| High-level output voltage | V _{OH} | V _{CC} = MIN, V _{IH} = 2.0V V _{IL} = 0.8, I _{OH} = MAX | 2.4 | | V |
| Low-level output voltage | V _{OL} | V _{CC} = MIN, V _{IH} = 2.0V V _{IL} = 0.8, I _{OL} = MAX | | 0.5 | V |
| Input current at max input voltage | I _I | V _{CC} = MAX, V _I = 5.5V | | 1.0 | mA |
| High-level input current | I _{IH} | V _{CC} = MAX, V _I = 2.4V | | 10 | uA |
| Low-level input current | I _{IL} | V _{CC} = MAX, V _I = 0.4V | | -10 | uA |
| Quiescent Current ¹ | I _{ccq} | V _{dd} = MAX | | 100 | uA |
| Operating Current | I _{cco} | V _{dd} = 5V +/- 5% | | 10 | mA |

1 - Measured with inputs at V_{dd} or V_{ss}, outputs floating



ATARI CORP.

1196 Borregas Ave.

San Jose, CA 95128

SIZE

DRAWING NO.

CO61618A-XX

REV

A

SCALE

SHEET 9 OF 12

3.8 Switching Characteristics
(TA=0 degrees C TO 70 degrees C, VCC=5.0V +/- 5%)


| PARAMETER | SYMBOL | MAX | UNIT |
|--|--------|-----|------|
| Input valid to output valid pins 12, 13, 15, 19 | tpd | 40 | ns |
| Input valid to output valid pin 17 | tpd | 35 | ns |
| Input valid to output valid pin 16 | tpd | 70 | ns |

*Inputs are pins 1-9, 11, 14, 18

*C_L = 45pF

See Standard Test Load and Definition of Waveforms below.

SWITCHING WAVEFORMS



- NOTES:
1. All voltages measured with respect to Pin 10 (VSS) of device.
 2. Outputs are guaranteed stable after maximum specified delays.



ATARI CORP.

1196 Borregas Ave.

San Jose, CA 95128

SIZE

DRAWING NO.

CO61618A-XX


REV

A

SCALE

SHEET 10 OF 11

AC TEST LOAD



NOTES:

1. Typical limits are at $V_{CC}=5.0V$ and $T = 25^{\circ}C$
A
2. tpd is tested with $C = 45pF$
L

4.0 PACKAGE CONFIGURATION

Package configuration shall conform to the requirements of drawing C099931 Dual in-line package.

5.0 MARKING

The part shall be marked with manufacturer's name or logo, type number, lot date code, and Pin Number 1 identification. Lot date code shall be on top.

6.0 QUALITY ASSURANCE PROVISIONS

Must meet the ATARI Specification C099901, "Qualification, Reliability Acceptance Specification".

7.0 PACKAGE FOR SHIPMENT

All parts shipped to this specification shall be packed in accordance with C099901 to prevent physical damage, corrosion, static discharge and deterioration during shipment.



ATARI CORP.

1196 Borregas Ave.

SIZE

DRAWING NO.

C061618A-XX

REV

A

SCALE

SHEET 11 OF 11